

EVEREST

ENGINE GUARD BAG

USER MANUAL



FURCHTLOS

INCLUDED

EVEREST Engine Guard Bag
x1



Detachable shoulder strap
x1



CLOSING THE BAG

- 1 Roll the mouth of the bag at least three times for a watertight seal. Then fasten the buckles on either side of the bag and pull the webbing ends to tighten the straps. After tightening, the excess webbing length can be folded and secured with the hook and loop strip at the end of the webbing.



ASSEMBLY TO THE ENGINE GUARD



NOTE: Assembly to the engine guard may vary slightly by motorcycle model. The user is responsible for selecting the appropriate fixation points for their own motorcycle and ensuring the bag is securely fastened before operating the vehicle.

- 1 Unhook the G-hooks from the front MOLLE webbing panel and slide the straps out of the slots on the side of the bag.



- 2 Holding the engine guard bag in the desired position, wrap the fixation strap around the engine guard or other fixation point. The strap can be wrapped more than once for a more secure fitment.



- 3** Pass the webbing strap back through the slots on the side of the bag, rehook the G-hook into the MOLLE webbing panel on the front, and pull the loose webbing end to tighten the strap.



- 4** Repeat steps 2-3 with all 4 straps. Once the bag is attached in the desired position and all the straps have been tightened, fold the loose webbing ends and secure them with the elastic bands on each strap.



ASSEMBLY TO THE REAR RACK



NOTE: Assembly to the rear rack may vary slightly by motorcycle model. The user is responsible for selecting the appropriate fixation points for their own motorcycle and ensuring the bag is securely fastened before operating the vehicle.

- 1** Unhook the G-hooks from the front MOLLE webbing panel and slide the straps out of the slots on the side of the bag.



- 2** Place the bag in the desired position on the rear rack.



- 3** Pass the webbing strap through the integrated fixation point on the support plate or around the tube of the rear rack, then back through the slot on the side of the bag. Rehook the G hook into the front MOLLE webbing panel and pull the webbing end to tighten the strap.



- 4** Repeat step 3 with the remaining straps. Once the bag is attached in the desired position and all the straps have been tightened, fold the loose webbing ends and secure them with the elastic band. Ensure the bag is securely attached before each operation of the vehicle.



WARNINGS & GUIDELINES

WARNING!

Please read the user manual carefully and follow the recommended assembly method.

It's recommended to check that the bag is securely attached before each operation of the motorcycle.

Do not drive the motorcycle with a bag that is not fully closed, is not properly secured, or in any other condition that may affect the safe operation of the vehicle.

Ensure that no part of the bag, including the fixation straps or other accessories, has close contact with high temperature areas such as the exhaust pipe.

CLEANING & MAINTENANCE

To maintain a nice appearance, it's recommended to use silicone lubricant spray and a soft cloth to wipe the bags clean.

Do not use harsh cleaning agents, chemicals or high pressure cleaners.

When the surface material is exposed to direct sunlight for a long time or is affected by environmental factors (such as haze, acid rain, etc.), the color may fade or change.

If the product is contaminated with gasoline or similar substances it must be cleaned immediately!

FURCHTLOS does not assume any responsibility for product damage and color change caused by improper cleaning and maintenance!



CLEAN WITH A DAMP CLOTH OR
SOFT SPONGE



DO NOT PRESSURE WASH



CLEAN GASOLINE OR OTHER
SPILLS IMMEDIATELY!



DO NOT USE CHEMICALS OR HARSH
CLEANING AGENTS



VIDEO TUTORIAL



WARRANTY REGISTRATION



FOLLOW & TAG US
@FURCHTLOSMOTO

www.furchtlos-moto.com